

Rotoguard

An ideal protection scheme for synchronous machine rotors

Lack of maintenance, operational knowledge or monitoring systems can cause catastrophic failures in large machines and with this in mind, experts at Quartzelec have designed a state of the art system which provides protection, operational information and ongoing monitoring, allowing detection of early signs of rotor winding insulation deterioration.

ATEX certified, Quartzelec's Rotoguard is a telemetry system designed for monitoring and protecting the rotor winding of synchronous machines. It enables a true measure of fault resistance from 100k Ω to 500 Ω to be made, without any influence from the DC field component of excitation. By giving an early warning of deterioration of the rotor insulation and providing a continuous readout of the rotor earth leakage resistance, the system forms the basis for an ideal protection scheme for synchronous machine rotors.

Being separately powered, the system is active at all times. It can detect deterioration in insulation resistance due to condensation when a machine stands idle for an extended period. Alternatively, it can also detect insulation resistance during acceleration to speed.



Key Benefits

- Can be retrofitted to most over hung exciters
- With the addition of a shaft mounted current shunt, Rotor Current and Rotor Winding Temperature are displayed in addition to Earth Leakage and Rotor Voltage values
- Monitors for earth fault whilst machine is stationary and during run-up as well as during normal operation
- No sliprings or brushes means reduced maintenance
- Certified for hazardous area applications
- A continuous stream of instantaneous readings updated every four seconds
- Data log of one-minute averages for the previous twenty-four hours
- Data can be downloaded to a PC and the time history of the rotor operating conditions examined in the event of a machine breakdown
- Four isolated 4-20mA loops for remote display of voltage, current, temperature and leakage
- The Rotor Module is designed to accommodate a purpose built optional Encapsulated RC unit

Specification

Display	800x400 TFT touch screen colour display. 'Modules Healthy' green indicator on the display will flash once every 4 seconds when communications are healthy.
Outputs	4-20mA loops: - Voltage - Current - Leakage resistance - Temperature Earth Fault (Trip) Relay Output Programmable Relay Output: - Overvoltage - Overcurrent - Earth Fault (Warning) - Overtemperature USB port to connect to a PC (Mini USB 'B', IP68)
Earth fault level	0 to 100kΩ, user adjustable (Default setting 5kΩ)
Operation time	4 seconds maximum, (temperature averaged over 12 readings)
Max. field voltage	Continuous ± 600V DC Transient ± 1000V DC
Cable types	Distance between machine mounted unit and Rotoguard Monitor: Power: - Up to 100m: 2 core 2.5mm ² - Up to 300m: 2 core 4.0mm ² Signal: - Up to 300m: Coax RG223/U
Output relay rating	3 Amps maximum (250V AC) (resistive) 0.5A max (50V DC) (resistive)
Input Voltage	100-240Vac, 50-60Hz, Input fuse: UL/IEC127 250 Vac S 3.15 A
Rack dimensions	3U 19 inch rack
Certifications	Sira 03ATEX4219U CSAE 22UKEX1420U IECEx SIR 14.0005U (Ex ec mc IIC Gc)

Supported by a team of electrical and mechanical engineers, you can rely on Quartzelec for all your equipment monitoring requirements. Contact us to discuss your next project or to find out more about our range of products and services.

Key Contact Information

To request a quotation or further information please contact

Quartzelec Rugby

+44 (0)1788 512512

rugby@quartzelec.com



T: +44 (0)1788 512512 | E: info@quartzelec.com | www.quartzelec.com